

Roof Hatch Barrier Technical Data Sheet

Description

Sellwood Roof Hatch Barriers provide a pipe clamp barrier around Sellwood Roof Hatches, to prevent the risk of falling back through the roof hatch opening, in compliance with MBIE's "Best practice guidelines for working at height in New Zealand - 6.2 Edge protection". Sellwood Roof Hatch Barriers fix directly to Sellwood Roof Hatches without the need for additional roof penetrations. Roof Hatch Barriers provide safety when entering and exiting the roof hatch, as well as when working on the roof.

Roof Hatch Barrier Range

Model	Suitable for Sellwood Roof Hatch
RHB900700	SRH900700
RHB800800	SRH800800
RHB1200700	SRH1200700
RHB1200900	SRH1200900
RHB1500700	SRH1500700

Specification

"Roof Hatch Barrier shall be an RHB... available from Sellwood Products."

Features

- Full barrier protection around roof hatch opening
- Durable high gauge steel
- Pre-designed to fit the Sellwood Roof Hatch (SRH) range
- Allen key pipe clamping system for easy on site installation

Materials

- Pipe clamps: galvanised cast iron
- Pipe 25NB: galvanised steel
- Finish: galvanised

Compliance

The Sellwood Roof Hatch Barrier is designed to meet the MBIE "Best practice guidelines for working at height in New Zealand July 2019" - 6.2 - Edge protection

The Sellwood Roof Hatch Barrier complies with NZBC Clause F4 / AS1 – Safety from Falling 1.1.1 – Table 1 Minimum Barrier Heights - 1100mm and 1.2.2 Barrier Construction - b) "460mm vertically between longitudinal rails"

Downloads (sellwood.co.nz/downloads)

Brochures, Installation Instructions, Technical Drawings, Specifications, Technical Data Sheets & Safety Data Sheets

Warranty

The Sellwood Roof Hatch Barrier Warranty is 5 Years from date of purchase. Warranty is subject to installation and usage in accordance to Sellwood Products specifications.

