

Retractable Ladder (Commercial) Technical Data Sheet

Description

The Sellwood range of heavy duty, commercial Aluminium Retractable Ladders provide safe, easy access onto roofs, mezzanine floors and platform areas at height, where the landing area below needs to be kept clear of obstruction. The unique spring and stay system allows the ladders to be easily pulled down from the ceiling and folded back up when not in use. The heavy duty aluminium ladder and steel componentry allow for longevity in a commercial environment. The standard Sellwood Aluminium Retractable Ladder range is suitable for heights up to 3.6 meters.

Retractable Ladder (Commercial) Range

Model	Ceiling Height	Opening Required	Weight
A25	2300mm – 2500mm	1220mm x 650mm	34Kg
A28	2550mm – 2800mm	1370mm x 650mm	37Kg
A31	3000mm – 3160mm	1440mm x 650mm	41Kg
A34	3250mm – 3400mm	1525mm x 650mm	44Kg
A36	3500mm – 3660mm	1525mm x 650mm	44Kg

Specification

"Retractable Ladder shall be an A... available from Sellwood Products."

Features

- Designed in New Zealand
- Heavy duty anodised aluminium ladder
- Unique spring system takes the full weight of the ladder
- Heavy duty steel componentry
- Available in heights up to 3.6 meters
- 300kg load rating
- 70° climbing angle
- 2nd Stage Springs over 3 meters for ease of use

Materials

- Stringer: aluminium 2mm channel extrusion
- Tread: aluminium grip tread 70° angled extrusion
- Finish: anodised aluminium
- Lid: 9mm MDF
- Hardware finish: Zinc passivated
- Ladder feet: rubber universal non marking
- Rivets: steel 4.8mm 6-3 domed

Compliance

Sellwood Retractable Ladders (Commercial) comply with the NZBC D1-Access-Routes-2nd-Edition-amendment 6 - Jan 2017 regulations for "retractable ladders to lofts and attics in housing and for maintenance access in other buildings."

Downloads (Click Here)

Brochures, Installation Instructions, Technical Drawings, Specifications, Technical Data Sheets & Safety Data Sheets

Warranty

The Sellwood Retractable Ladder (Commercial) Warranty is 5 Years from date of purchase. Warranty is subject to installation and usage in accordance to Sellwood Products specifications.

