

Description

The Sellwood range of Roof Hatch Barriers (RHB) keep workers safe while working on roofs by providing a perimeter barrier around the Sellwood Roof Hatch (SRH), in accordance with WorkSafe NZs guidelines for working at height. The range of Sellwood Roof Hatch Barriers are specially designed to fit the Sellwood Roof Hatch (SRH) range, with associated barriers for each roof hatch. The Sellwood Roof Hatches and Roof Hatch Barriers are pre-drilled making for easy installation on site.

Roof Hatch Barrier Range

| | |
|------------|----------------------------------|
| Model | Suitable for Sellwood Roof Hatch |
| RHB650900 | SRH650900 |
| RHB800800 | SRH800800 |
| RHB1150650 | SRH1150650 |
| RHB1200900 | SRH1200900 |
| RHB1525650 | SRH1525650 |

Specification

"Roof Hatch Barrier shall be an RHB... available from Sellwood Products Ltd."

Features

Full barrier protection around roof hatch opening
 Pre-designed to fit the Sellwood Roof Hatch (SRH) range
 Allan key pipe clamping system for easy on site installation

Materials

Pipe Clamps: Galvanised Cast Iron
 Pipe 25NB: Galvanised steel
 Finish: Galvanised

Compliance

The Sellwood Roof Hatch Barrier is designed to meet the MBIE "Best practice guidelines for working at height in New Zealand April 2012" - 6.2 - Edge protection

Installation

Download full installation instructions from www.sellwood.co.nz

Warranty

The Sellwood Roof Hatch Barrier Warranty is 10 Years from date of purchase. Warranty is subject to installation and usage in accordance to Sellwood Products specifications.

