Description

The Sellwood range of Pivotal Ladders - Aluminium (PLA) provide safe, easy access onto roofs, mezzanine floors and platform areas that are at height. The pivoting system at the top of the ladder allows for the ladder be pivoted from a 70° angle when in use to a 90° angle when not in use, creating clear space at the base of the ladder. The Sellwood PLA Ladders are custom designed, manufactured to suit each application and available in any height, up to 4m

Pivotal Ladder Range

Model	Height	Weight Approx.	Handrails
PLA1000	Up to 1000mm	4kg	X
PLA1000-2000	1000mm - 2000mm	4kg – 10kg	X
PLA2000-3000	2000mm - 3000mm	10kg – 16kg	\checkmark
PLA3000-4000	3000mm - 4000mm	16kg – 21kg	\checkmark
PLA4000-5000	4000mm - 5000mm	21kg – 26kg	\checkmark

Specification

"Pivotal Ladder shall be a PLA... available from Sellwood Products Ltd."

Features

Heavy duty grip treads 300kg load rating 70° climbing angle Ladder - anodised aluminium finish Built to height as required Design and manufactured in NZ

Materials

Stringer: anodised aluminium 2mm channel extrusion Tread: anodised aluminium grip tread 70° angled extrusion Handrail: aluminium 50mm OD round tube extrusion Fixing brackets: aluminium unequal angle extrusion Bracing gussets: steel 180mm silver passivated Ladder feet: rubber universal non marking

Rivets: steel 4.8mm 6-3 domed

Compliance

Sellwood Pivotal Ladders comply with NZBC D1/AS1 5.0 - Fixed Ladders

Installation

Download full installation instructions from www.sellwood.co.nz

Warranty

The Sellwood Pivotal Ladder Warranty is 10 Years from date of purchase. Warranty is subject to installation and usage in accordance to Sellwood Products specifications.

