

Retractable Ladder (Commercial) Technical Data Sheet

Description

The Sellwood range of heavy duty, commercial Aluminium Retractable Ladders provide safe, easy access onto roofs, mezzanine floors and platform areas at height, where the landing area below needs to be kept clear of obstruction. The unique spring and stay system allows the ladders to be easily pulled down from the ceiling and folded back up when not in use. The heavy duty aluminium ladder and steel componentry allow for longevity in a commercial environment. The standard Sellwood Aluminium Retractable Ladder range is suitable for heights up to 3.6 meters.

Retractable Ladder (Commercial) Range

Model	Ceiling Height	Opening Required	Weight
A25	2300mm – 2500mm	1400mm x 650mm	34Kg
A28	2550mm – 2800mm	1400mm x 650mm	37Kg
A36	2800mm – 3660mm	1400mm x 650mm	44Kg

Specification

“Retractable Ladder shall be an A... available from Sellwood Products.”

Features

- Designed in New Zealand
- Heavy duty anodised aluminium ladder
- Unique spring system takes the full weight of the ladder
- Heavy duty steel componentry
- Available in heights up to 3.6 meters
- 300kg load rating
- 70° climbing angle
- 2nd Stage Springs over 2.8 meters for ease of use

Materials

- Stringer: aluminium 2mm channel extrusion
- Tread: aluminium grip tread 70° angled extrusion
- Finish: anodised aluminium
- Lid: 30mm pine frame with 30mm polystyrene infill and 3mm MDF sheet cover both sides.
- Hardware finish: Powder coated
- Ladder feet: rubber universal non marking
- Rivets: steel 4.8mm 6-3 domed

Downloads (sellwood.co.nz/downloads)

Brochures, Installation Instructions, Technical Drawings, Specifications, Technical Data Sheets & Safety Data Sheets

Warranty

The Sellwood Retractable Ladder (Commercial) Warranty is 5 Years from date of purchase. Warranty is subject to installation and usage in accordance to Sellwood Products specifications.

