

Specifications

| Range | Premier | | Deluxe | | | Truss |
|------------------|-----------|-----------|-----------|-----------|-----------|-----------|
| Model | P30 | P36 | D28 | D30 | D36 | Q24 |
| Ceiling Height | 2250-3050 | 3050-3660 | 2250-2800 | 2800-3100 | 3100-3660 | 2250-2440 |
| Opening Required | 1300x600 | 1300x600 | 1400x650 | 1450x650 | 1450x650 | 835x650 |
| Max Load | 200kg | 200kg | 250kg | 250kg | 250kg | 200kg |
| Angle | 68° | 68° | 63° | 63° | 63° | 70° |
| Material | Timber | Timber | Timber | Timber | Timber | Timber |
| Tread Profile | | | | | | |
| Tread Depth | 80 | 80 | 120 | 120 | 120 | 80 |
| Ladder Width | 380 | 380 | 430 | 430 | 430 | 430 |
| Landing Space | 1095-1414 | 1418-1667 | 1337-1634 | 1362-1770 | 1770-2055 | 1005-1076 |
| Projection | 1770 | 1763 | 1854 | 1994 | 1995 | 1238 |
| Stack Height | 320 | 410 | 400 | 400 | 525 | 420 |
| Handrail | ✓ | ✓ | ✓ | ✓ | ✓ | - |
| Rubber Feet | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Insulated Lid | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Warranty (years) | 15 | 15 | 15 | 15 | 15 | 15 |

Uses **Residential**

| Range | Commercial | | |
|------------------|------------|-----------|-----------|
| Model | A25 | A28 | A36 |
| Ceiling Height | 2300-2450 | 2550-2700 | 2700-3660 |
| Opening Required | 1400x650 | 1400x650 | 1400x650 |
| Max Load | 200kg | 200kg | 200kg |
| Angle | 70° | 70° | 70° |
| Material | Aluminium | Aluminium | Aluminium |
| Tread Profile | | | |
| Tread Depth | 100 | 100 | 100 |
| Ladder Width | 425 | 425 | 425 |
| Landing Space | 1088-1141 | 1180-1232 | 1232-1581 |
| Projection | 1517 | 1621 | 1777 |
| Stack Height | 423 | 423 | 529 |
| Handrail | ✓ | ✓ | ✓ |
| Rubber Feet | ✓ | ✓ | ✓ |
| Insulated Lid | ✓ | ✓ | ✓ |
| Warranty (years) | 5 | 5 | 5 |

Uses **Commercial**

