














# ATTIC LADDER SPECIFICATIONS

Range	Premier	Regular			Deluxe			Truss
Model	P30	R28	R31	R36	D28	D31	D36	Q24
Ceiling Height	2250-3050	2250-2800	2750-3100	3100-3660	2250-2800	2750-3100	3100-3660	2250-2440
Opening Required	1300x600	1370x650	1370x650	1440x650	1400x650	1440x650	1440x650	835x650
Max Load	200kg	200kg	200kg	200kg	250kg	250kg	250kg	180kg
Angle	68°	70°	70°	70°	63°	63°	63°	70°
Material	Timber	Timber	Timber	Timber	Timber	Timber	Timber	Timber
Tread Profile								
Tread Depth	80	90	90	90	120	120	120	80
Ladder Width	380	430	430	430	430	430	430	430
Projection	1770	1554	1733	2028	1854	2020	2039	1224
Landing Space	1415	1182	1298	1498	1635	1769	2071	1037
Handrail	✓	✓	✓	✓	✓	✓	✓	-
Rubber Feet	✓	-	-	-	✓	-	-	-
Insulated Lid	✓	-	-	-	✓	-	-	-
Warranty (years)	15	10	10	10	15	10	10	10
Uses	Residential				Residential & Light Commercial			Residential

Range	Commercial				
Model	A25	A28	A31	A34	A36
Ceiling Height	2300-2500	2550-2800	3000-3160	3250-3400	3500-3660
Opening Required	1220x650	1370x650	1440x650	1525x650	1525x650
Max Load	300kg	300kg	300kg	300kg	300kg
Angle	70°	70°	70°	70°	70°
Material	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
Tread Profile					
Tread Depth	100	100	100	100	100
Ladder Width	425	425	425	425	425
Projection	1467	1589	1801	1892	2027
Landing Space	1092	1201	1332	1420	1514
Rubber Feet	✓	✓	✓	✓	✓
Warranty (years)	5	5	5	5	5
Uses	Commercial				

